


# MRO2041-4

## Applicable to a Variety of Water Quality

Switch knob to control waste water  
More flexible for different water quality



## Still Purifying Water Even if Power Cut Off



- + Still purifying water even if power cut off
- + One touch filter, easy filter replacement
- + Slim size, save more space for the cabinet
- + Applicable to a variety of water quality

Model	MRO2041-4
Color	white
Power Supply Voltage & Frequency (V/Hz)	100-240V/50-60Hz
Power Comsumption	30W
Purification Capacity (L/h)	7.9L/h
Total Water Tank Capacity (lt)	3.5L (2.5G pressure pot) 6L (3G pressure pot)
Pure Water Output with power	≥0.13L/min
Pure Water Output without power	≥0.8L/min
First Stage Filter & Life Time	PP:3600L
Second Stage Filter & Life Time	C:7200L
Third Stage Filter & Life Time	RO:7200
Forth Stage Filter & Life Time	C2 T33:3600
Pouvoir Hydrogène--PH	6.5~8.5
Applicable Environment	4~38℃
Applicable Water Pressure	0.1~0.4 Mpa (without pump & power off> 0.2MPa)
Feed Water Temperature	4~38℃
Applicable Feed Water	TDS≤350ppm
particular removable	0.001~0.0001 μ m
Chlorine Reduction	≥90%
Colon Bacillus	≥99.99%
Product Dimensions (mm)	W206*D266*H380