

TOP-LOADING
YL1241AS

FEATURES

- Fashionable design
- Double safety device for preventing overheat
- Child safety lock for hot water faucet
- High efficiency compressor cooling
- High power stainless steel hot water tank and stainless steel cold water tank
- Anti-overflow bottle supporter
- No cabinet



TOP-LOADING
YL1241AS

Voltage / Frequency	220~240V/50~60Hz
Cooling Method	Compressor
Heating Method	Internal Element
Compressor Coil material	Aluminum(A) Copper(B)
Refrigerant type and weight	R134a/32g
Sound (dBA)	≤55dB
Heated water temperature -(°C)热水温度	≥85°C
Heated water capacity min at 25 (°C) Ambient (L/hr)	4L/H
Chilled water temperature - nominal - (°C)/	≤10°C
Chilled water capacity min at 25 (°C) Ambient (L/hr)	2L/H
heating watts (W)	420W
Cooling watts (W)	100W
Water Supply	Bottle Water
Flow Rate - Minimum (each faucet)	TBC
Chilled water	≥1.2L/Min
Room Temperature Water	/
Hot Water 热	≥1.2L/Min
Typical Operating Ambient Temperature	10-38°C
Operating Humidity	≤90%
Chilled water	Y
Ambient water	/
Hot Water	Y
Water Spouts	2



on the left

